Assembly Instructions for Twin Top



MOUNTING LOCATIONS

Assembly Instructions for Rear Canopy

Note: Rear canopy fabric has light hole in rear and zipper across front.

IMPORTANT: It is crucial to carefully follow these instructions in order!

1 Stretch the fabric out flat on a clean dry surface upside down and find the rear by locating the pre-cut hole for the stern light. SEE FIG. 1



4 Locate the 6" joiner pieces. Attach 4 joiners into the bows on what will be the wired side of the frame only for now. Attach the joiner pieces to the center bow pieces with the tech screws provided. (2 screws per side) Note: joiner piece extends approx. 3" into each piece. SEE FIG. 4



2 Locate the rear center bow piece (It has the pre-drilled hole in the center for the stern light wire.) and insert it into the rear sleeve of the canopy. **SEE FIG. 2**



3 Insert the other 3 center bow

of the canopy.

SEE FIG. 3

pieces into the remaining 3 sleeves

5 Slide one end of the wire harness through the white plastic grommet (**FIG. 5**), then insert the same end into the pre-drilled hole in the center bow piece (**FIG. 6**). Feed the wire completely through until it comes out the opposite end (**FIG. 7**). Push grommet into hole (**FIG. 8**).



6 Slide the wire into the top (open end of the radius) of the bow with the pre-drilled hole in its base. Feed the wire through the entire length of the bow until it exits the base. SEE FIG. 9



NOTE: (2 people suggested for Step #11)

Place the assembled canopy and frame into main deck mounts and line up the pre-drilled holes in both the frame and deck mounts. Insert the pull pins provided. **SEE FIG. 11.** Do this for main mounts only. Let rear struts dangle free.



13 Find center extension piece and zip to front and rear canopy.

Due to the different rail configurations, it may be necessary to shorten rear struts. To do so, **detach at top**, cut off with hacksaw to desired length, drill hole and reattach. Level the top by loosening the front straps. Your assembly is now complete. 7 Spread the wired side of the frame apart and line up its bows with their center pieces in place in the canopy sleeves. (Strut to the rear, straps to the front.) Secure the bows and center pieces with tech screws. SEE FIG. 14 BELOW

8 Attach the last 4 joiner pieces in the bows opposite the wired side of the frame and repeat STEP #8 until frame is completely assembled with canopy attached. SEE FIG. 14 BELOW

9 Repeat STEPS #1, 3 & 4 for front frame assembly. **Note:** Front canopy fabric has the zipper across rear.

For mounting locations on your boat, refer to front page of this instruction sheet. When installing the deck mounts, mark the position for the 2 holes on the top rail, and drill completely through the rail. **SEE FIG. 10**



Locate the attached front straps and stretch them forward along the top rails to position the strap eyes. Mark the holes and attach with ovalhead bolts. Do not locate them in front of the gate or obstruct the gateway. Snap the snap hooks to the strap eyes. **SEE FIG. 12-13**



